



## Review On Hydrogen Production and Storage

K.Uma devi\*

\*Department of Humanities and Sciences, Annamacharya Institute of Technology and Sciences, Autonomous Rajampet

\*Corresponding Author: K.Uma devi

\*Email: reachumakandukuri@gmail.com

### Abstract:

Hydrogen production is influenced by various factors, including durability, charge/discharge rates, refilling time, storage duration without loss, faster response, transient response, fuel quality, efficiency, safety, confirmability, weight, and volume. Several methods contribute to hydrogen production, such as the utilization of  $\text{TiO}_2$  nano material as a photo catalyst in the hydrogen evolution process, leveraging its commendable physical and chemical properties. Graphene, with its excellent thermal, mechanical, and physical properties, also plays a crucial role in hydrogen production and storage. Other methods encompass autothermal reforming, steam methane reforming, partial oxidation, electrolysis for water splitting, gasification of coal, natural gas reforming, employment of nano materials, nuclear power, solar energy, wind energy, lithium-ion and sodium-ion batteries, biomass, algae, and advanced natural gas conversion plants.

Hydrogen serves as a clean fuel alternative for transportation, mitigating environmental pollution compared to conventional petrol usage. Storage of hydrogen occurs through physical and chemical means. The statement that "storing hydrogen at pressure will not cause any more significant safety issues than liquid fuel" is supported, highlighting the intrinsically safe design of storage systems even in the face of ballistic penetration or explosion events. This paper provides an in-depth review of various hydrogen production methods, emphasizing the generation of substantial quantities of hydrogen, and explores diverse storage approaches.

**Key Words:**  $\text{TiO}_2$ , Photo catalysis, Steam Methane, Gasification, Biomass, Wind Energy, Graphene.

### Introduction:

The escalating growth in global population has led to a surge in energy demand. Hydrogen, serving as a potent energy carrier, plays a pivotal role as a fuel for transportation. It can be derived from both renewable and non-renewable resources. Renewable sources encompass air, water, soil, wood, solar energy, wind energy, among others. On the other hand, non-renewable sources include fossil fuels like coal, petroleum, natural gas, and rare minerals often found in meteorites.

The utilization of non-renewable fossil fuels for energy production has resulted in the significant release of  $\text{CO}_2$  gas, exacerbating environmental concerns. In addressing this issue, hydrogen emerges as an ideal solution to mitigate greenhouse gas emissions, offering a cleaner alternative to conventional energy sources.

### 2. Production Methods of Hydrogen:

#### 2.1 $\text{TiO}_2$ as a Catalyst for Hydrogen Production:

Since the 1970s,  $\text{TiO}_2$  has served as a photo catalyst in hydrogen production, boasting attributes such as low cost, abundance in the Earth's crust, stability, excellent optical and electronic properties, high photo catalytic activity, chemical stability, non-toxicity, and environmental friendliness. Studies have demonstrated the effectiveness of  $\text{TiO}_2$ -based photo catalysts, showcasing a hydrogen production rate of  $11400 \mu\text{mol}/\text{gh}$ . Research suggests that modifying  $\text{TiO}_2$  with different materials can enhance its photo catalytic activity.


Given  $\text{TiO}_2$ 's need for increased surface area, it exists in two distinct phases: anatase and rutile. In comparison, the anatase phase proves more efficient for the hydrogen evolution reaction due to its band gap between the conduction and valence bands. The band gap of the anatase phase is eg: eV, while that of the rutile phase is eg: eV. Combining  $\text{TiO}_2$  with graphene further improves its catalytic properties, as graphene exhibits favorable optical and electrical characteristics with a zero band gap between the valence and conduction bands.

#### 2.2. Photocatalysis Process for Hydrogen Production:

The photocatalysis process for hydrogen production involves the following steps in the splitting of water through UV-visible radiation:

1. The photocatalyst absorbs solar energy, producing excitons that are equal to the band gap between  $\text{TiO}_2$ 's valence and conduction bands.
2. From the valence band to the conduction band, electrons are transferred.
3. The liberated electrons are absorbed by  $\text{TiO}_2$ , which produces hydrogen. Through the oxidation of water, photons received on the  $\text{TiO}_2$  surface help produce oxygen.

Equations:



### 2.3 Steam Methane Reforming:

In the steam methane reforming process, hydrogen, carbon monoxide, and a negligible amount of carbon dioxide are produced when methane and steam react at 3 to 25 bar pressure (1 bar = 14.5 psi) in the presence of a Ni and Pt catalyst. For this endothermic process to continue, heat must be supplied.

Around the world, steam reforming produces about 95% of hydrogen, making it the least expensive process in terms of capital costs. It is now the most advanced technology for producing hydrogen. The emission of greenhouse gases into the atmosphere, namely carbon dioxide and carbon monoxide, is a significant disadvantage of steam methane reforming. Steam methane reforming is still commonly used since it is inexpensive and produces hydrogen with a high purity, even with this shortcoming. This approach yields hydrogen that is pure enough to be used in fuel cells and large-scale industrial processes.

### 2.4: Gasification of Coal:

Gasification converts coal into a very hot synthesis gas, also known as Syn gas, which may reach temperatures of up to 1800 degrees Celsius. Syn gas is mostly made up of carbon dioxide, hydrogen, and minor amounts of other gases and particles. Pulverized coal is combined with an oxidant—typically steam, air, or oxygen—to achieve this. By reacting steam and carbon monoxide from the syngas mixture in the presence of iron and chromium as catalysts, one can enhance the amount of hydrogen produced during coal gasification. Direct hydrogen production from coal is possible with carbon capture and storage, resulting in almost no greenhouse gas emissions. Growing biomass removes carbon dioxide from the environment, and using biomass gasification to produce hydrogen results in almost zero net greenhouse gas emissions without carbon capture and storage.

Since gasification produces fewer emissions of CO<sub>2</sub> and other pollutants than incineration, it is frequently regarded as the most environmentally beneficial technique of turning garbage into energy. Because of this, it is a sustainable choice for producing energy and managing trash. Three different types of ash can be produced by coal gasification: fly ash, bottom ash, and slag. The majority of the solid waste is converted into slag for use in gasifiers at high temperatures. The byproducts of non-slugging gasification are fine fly ash and coarse bottom ash. The fact that coal gasification releases a lot more carbon dioxide than other processes is a drawback.

One benefit of gasifying coal is that it makes it easier to exploit its chemical characteristics, which are useful for producing chemical feedstocks and power. Chemicals like urea and ammonia, as well as methanol, can be produced by the gasification process. They are regarded as the foundation for numerous fertilizers. Gasification is also useful in the production of fuel from biomass, coal, oil, and sands for transportation. A fuel gas rich in CO and H<sub>2</sub> is the primary byproduct of coal gasification; other byproducts may include carbon dioxide (CO<sub>2</sub>), methane (CH<sub>4</sub>), water vapor (H<sub>2</sub>O), and nitrogen (N<sub>2</sub>), depending on the feedstock. The product gases undergo additional separation and purification in accordance with the needs of the various applications.

When biomass gasification is employed, which consumes carbon dioxide from the atmosphere, Gasification raises the temperature of coal to up to 1800 degrees Celsius, generating syngas, a high-temperature synthesis gas. Hydrogen, carbon dioxide, carbon monoxide, and trace amounts of other gases and particles make up this syngas. Pulverized coal is combined with an oxidant usually steam, air, or oxygen during the process. By reacting the carbon monoxide in the syngas mixture with steam in the presence of a catalyst, such as iron and chromium, the production of hydrogen from coal gasification can be improved. Nearly zero greenhouse gas emissions can be achieved by directly producing hydrogen from coal using carbon capture and storage.

Even without carbon capture and storage, this technique of producing hydrogen results in almost zero net greenhouse gas emissions. Compared to incineration, gasification is said to be a more environmentally beneficial method of turning trash into energy because it releases less CO<sub>2</sub> and other pollutants. Because of this, it is a sustainable choice for producing energy and managing trash.

Fly ash, bottom ash, and slag are the three types of ash produced by coal gasification; in high-temperature gasifiers, slag is the majority of the solid byproducts. Both fine fly ash and coarse bottom ash are produced by non-slugging gasification. Coal gasification is advantageous because it uses the chemical characteristics of coal to produce chemical feedstocks and generate energy, even though it emits more carbon dioxide than other processes. Methanol and other compounds that are essential to the production of several fertilizers, such urea and ammonia, can be produced by the gasification process. Moreover, gasification makes it easier to produce biomass, oil sands, and coal into transportation fuels.

Depending on the feedstock, the main byproduct of coal gasification is a fuel gas that is primarily rich in CO and H<sub>2</sub>, along with carbon dioxide (CO<sub>2</sub>), methane (CH<sub>4</sub>), water vapor (H<sub>2</sub>O), and nitrogen (N<sub>2</sub>). To satisfy particular application needs, the product gases go through additional separation and purification.

### 2.5 Hydrogen from Biomass:

On the other hand, enzyme-based biochemical processes, resembling "digesters," are currently The two different processes for producing hydrogen that are included in biomass technologies are the thermochemical process and the biochemical process. Because the thermochemical process operates at high temperatures, leading to increased reaction rates, it is thought to be a cost-effective method. With this process, biomass is cooked without the presence of oxygen, resulting in the production of a hydrogen-rich gas stream called "syngas" (which is made up of hydrogen and carbon monoxide). One possible approach is gasification or pyrolysis.

Restricted mostly to sugar-based, moist feedstocks. However, these processes might eventually use cellulosic feedstocks due to continuous improvements in systems and methodologies.

### 2.6 Hydrogen Production from Wind Energy:

Wind is a plentiful although erratic energy source that can power hydrogen production through water electrolysis. This hydrogen can be stored for use in fuel cells at a later time or utilized to power cars, especially in times when wind resources are scarce. Green hydrogen, in contrast to grey and blue hydrogen, is created by splitting water molecules through the electrolysis process utilizing renewable energy sources like solar and wind power.

Hydrogen is produced by electrolyzers using surplus solar and wind energy. Tanks and subterranean caves can be used to store the dispersed hydrogen, creating a network capable of energizing industries and serving as a backup for electric grids. An innovative approach involves offshore wind turbines with integrated electrolyzers, where hydrogen is produced at the base of each turbine and then transported to shore through dedicated pipelines. This integration maximizes the utilization of renewable energy and contributes to the sustainable production and use of hydrogen.

### 2.7 Hydrogen from Oil:

There are two approaches to hydrogen production based on the pyrolysis of hydrocarbons: one involves implementing the process close to the equilibrium state at elevated temperatures (around 800 degrees Celsius), while the other employs a non-equilibrium process at lower temperatures with an appropriate catalyst. In both cases, heat is used to "crack" the long hydrocarbon chains in oils into smaller fragments, yielding small amounts of hydrogen. 82–87 percent carbon and 12–15 percent hydrogen are commonly found in crude oil.

Partial oxidation is an ideal process for obtaining hydrogen from heavy oil, although the most prevalent method currently employed is steam reforming. In steam reforming, a light hydrocarbon, typically natural gas, serves as the feedstock. In the ensuing decades, fossil fuels—such as oil and natural gas—are anticipated to continue to be the primary sources of hydrogen generation. Almost half of all hydrogen produced worldwide comes via steam methane reforming, which is clearly the most economical industrial hydrogen generation technique. In this procedure, the gas is heated to temperatures between 700 and 1100 degrees Celsius while steam and a nickel catalyst are present.

India has ambitious plans to build electrolyser capacity ranging from 60 to 100 gigawatts to facilitate the production of green hydrogen. Government incentives aim to make green hydrogen more affordable, with the goal of reducing its production cost, currently estimated at 300-400 rupees per kilogram.

### 2.8 Hydrogen from Graphene:

Graphene serves multiple roles in hydrogen-related processes. It is utilized as a photocatalyst in the hydrogen evolution process owing to its effective physical, thermal, and mechanical properties. Additionally, graphene acts as a photocatalyst in the water-splitting process due to its high electron mobility property. In hydrogen storage, graphene nano-material is employed due to its porous nature, high surface area, and environmentally friendly properties. The versatility of graphene makes it a valuable material in various aspects of hydrogen production and utilization.

#### Hydrogen Storage:

Hydrogen storage employs two distinct methods: Physical storage and Chemical storage.

#### Physical storage:

1. Compressed Storage: In this method, hydrogen is kept as a gas in high-pressure tanks, usually with a pressure range of 350 to 700 bar (5000to10,000psi).
2. Liquid Storage: Since hydrogen has a boiling point of -252.8 degrees Celsius at 1 atmospheric pressure, liquid hydrogen storage requires cryogenic temperatures.

### 3. Adsorption-Based Storage:

2. Pressurized stationary or portable tanks and specialized hydrogen gas pipeline infrastructure can be used to store gaseous hydrogen in smaller volumes. Gaseous hydrogen storage is currently the most widely used technique for a variety of energy applications.

#### Chemical storage:

1. Metal Hydrides: These materials are useful for compactly and safely storing huge volumes of hydrogen. Transition metals make up reversible hydrides that function at room temperature and atmospheric pressure, which keeps the gravimetric hydrogen density below 3 mass percent.
2. Chemical hydrides: Involves chemically bonding hydrogen to specific compounds.

3. Liquid organic hydrogen carrier: Involves chemically binding hydrogen to organic compounds for storage and release.

Hydrogen storage materials play a crucial role in achieving higher density compared to gaseous and liquid hydrogen systems. Systems utilizing hydrogen storage materials are considered suitable for both onboard and stationary applications.

Metal hydrides, for instance, are effective at safely storing substantial amounts of hydrogen at ambient temperature and atmospheric pressure. However, the gravimetric hydrogen density is limited to less than 3 mass%.

Different methods can be employed for hydrogen storage, including high-pressure gas cylinders up to 800 bar, liquid hydrogen in cryogenic tanks at -253 degrees Celsius, adsorption on materials with a large specific surface area at less than 100 Kelvin, and absorption on interstitial sites in a host metal at ambient pressure. Despite being an excellent medium for renewable energy storage, hydrogen poses challenges due to its low volumetric energy density compared to other gases, requiring more space for storage.

Certain metals like platinum and palladium serve as storage media for hydrogen. Hydrogen can be stored in three main ways: as a compressed gas in high-pressure tanks, as a liquid in tanks or dewars, or as a solid by either absorbing or reacting with metals or chemical compounds, storing it in an alternative chemical form. Beyond being a fuel, hydrogen also functions as a storage medium. Various storage technologies with different capacities and discharge times are available, and underground hydrogen storage, utilizing caverns, salt domes, and depleted oil and gas fields, is considered the most cost-effective method. However, it's crucial to handle hydrogen with care, as it is an explosive and flammable gas.

Hydrogen, being colorless, odorless, and tasteless, is stored underground as the most economical method in all cases. Liquid hydrogen offers advantages over compressed gases for longer storage times. Numerous hydrocarbon fuels, such as natural gas, diesel, renewable liquid fuels, gasified coal, or gasified biomass, can be reformed to produce hydrogen. Presently, around 95% of all hydrogen is produced through steam reforming of natural gas.

Metal hydride storage functions by chemically bonding or absorbing hydrogen without the need for compression. Hydrogen, as an energy carrier, surpasses petrol and diesel in terms of weight. One kilogram of hydrogen contains 33.33 kWh of usable energy, while petrol and diesel only hold about 12 kWh/kg. Tanks made from composite materials, such as fiberglass, aramid, or carbon fiber with a metal liner (aluminum or steel), are used for storing hydrogen. This stored hydrogen can be retrieved as a backup energy supply when needed and can complement batteries in the transport sector.

Various metal hydrides, including magnesium hydride, sodium aluminum hydride, lithium aluminum hydride, lithium hydride, lanthanum nickel hydride, titanium iron hydride, ammonia borane, and palladium hydride, serve as sources of stored hydrogen. Cryogenic hydrogen storage, involving cooling hydrogen to extremely low temperatures (around -253 °C), faces challenges in maintaining this temperature. Despite lower efficiency and higher losses, hydrogen storage surpasses batteries in compensating for longer-term fluctuations, making it a versatile option for almost all sectors.

Tanks have a life cycle of 10 years, requiring a midterm inspection for safety reasons. The emissions from tank production can be spread over a significant quantity of hydrogen, depending on the frequency of filling and emptying events.

The levelized cost of hydrogen storage in depleted gas reservoirs, salt caverns, and saline aquifers with large-scale storage capacity is approximately \$1.15, \$2.50, and \$3.27 per kg of H<sub>2</sub>, respectively.

One notable advantage of hydrogen is its high gravimetric energy content, with a lower heating value (LHV) of 119.9 MJ/kg. Additionally, hydrogen is non-toxic, and its complete combustion produces only water (H<sub>2</sub>O). However, as a gas, hydrogen has a low energy density (0.089 kg/m<sup>3</sup>), and its storage is expensive. Despite this, hydrogen enables the storage of vast quantities of clean energy for extended durations, making it suitable for peak demand and seasonal energy balancing. Hydrogen can be generated from electrolysis using excess renewable electricity during peak production hours.

Currently, hydrogen is transported from the production point to the usage point via pipelines or over the road using cryogenic liquid tanker trucks or gaseous tube trailers. Pipelines are typically deployed in regions with substantial and stable demand, often exceeding hundreds of tons per day, and expected to remain consistent over decades.

**Solid State Storage: Absorption-Based Storage – Metal Hydrides:**

Integration of electrolyzers, metal hydride-based storage, and fuel cell systems has already reached cost competitiveness, even without economies of scale.

Further economies of scale are expected to reduce costs significantly.

The primary costs associated with electrolyzers, fuel cells, and storage systems are minimal.

The cost per kilogram of hydrogen (with 2wt% of hydride) is comparable to a 700-bar compressed hydrogen tank.

Solid-state storage is considered safer (low pressure) and offers higher volumetric density.

**Absorption-Based Storage – Metal Organic Frameworks (MOFs):**

Useful hydrogen weighing 5.6 kg can be stored in a dual-wall tank that has a liquid nitrogen (LN<sub>2</sub>) flow between the walls.

The tank comprises a 165 L inner aluminum vessel with a hexagonal heat transfer arrangement and 32 kg of MOF, with a total MOF vessel weight of 96 kg.

Additional Balance of Plant (BOP) peripherals include components for filling and delivery, temperature and pressure monitors and regulators, filters, connections for fuel cells, and heating.

Assuming the system is fully charged at 100-bar pressure and 77 Kelvin temperature.

The system costs \$6300 (for low-volume production) and \$3052 (for high-volume production). Component costs account for 53% in low-volume production and 39% in high-volume production.

#### **Liquid Hydrogen Storage:**

The cost of liquefaction ranges from \$50 million for 6000 kg/day to \$800 million for 200,000 kg/day. Cost models estimate approximately \$160 million for 27,000 kg/day, covering production, liquefaction, delivery, and dispensing.

The cost at the pump is \$14.25/kg H<sub>2</sub>.

The energy needed by industrial liquefiers is between 10 and 20 kWh/kg.

There are liquefiers operating in the United States that have capacities ranging from 6000 to 70,000 kg/day.

The Hydrogen Delivery Scenario Analysis Model (HDSAM) of the Department of Energy indicates that the capital expenses of liquefiers now range from 6000 to 200,000 kg/day, depending on their capacity.

#### **Compressed Hydrogen Storage:**

Offers high efficiency and discharge rates, with readily available fuel or feedstock.

Manufacturing is similar to Compressed Natural Gas (CNG) tanks, with differences in size, pressure, and production volume.

Hydrogen storage cost, compared to CNG, is primarily influenced by the Balance Of Plant (BOP) and composites.

BOP accounts for 50% of the cost for low production volumes and 25% for high volumes.

Hydrogen is stored at higher pressures (350 or 700 bar) compared to CNG (250 bar), requiring a significant amount of carbon fiber composite.

Type IV compressed hydrogen tank costs \$15 per kilowatt, providing 5.6 kg of usable hydrogen.

There are significant possibilities for cost reduction through the use of low-cost resin, carbon fibers, and a reduction in BOP costs.

#### **Geological Hydrogen Storage:**

Geological storage offers economies of scale, high efficiency, and cost-effectiveness.

Salt caverns are the lowest-cost option at \$0.6/kg H<sub>2</sub>, boasting an efficiency of 98%.

The U.S. possesses the largest salt cavern storage, equivalent to 30 days of Steam Methane Reforming (SMR) output, ranging from 10-20 thousand tonnes.

Depleted oil and gas reservoirs are larger than caverns but face challenges such as potential contamination.

Water aquifers represent a less mature technology.

Natural barriers, including trapping, reactions with microorganisms, and interactions with fluid and rock, play a crucial role.

Feasibility needs to be proven, but geological storage can offer seasonal storage solutions where salt caverns are unavailable.

It is less suitable for short-term and small-scale storage applications.

#### **Overview of Hydrogen:**

3. Hydrogen operations benefit from economies of scale.
4. Storage and transport play significant roles in the overall cost.
5. Costs are negligible when hydrogen is used close to its production source.
6. Ensuring the uninterrupted operation of the hydrogen value chain involves efficient storage solutions.
7. The choice of storage depends on factors such as volume, duration, cost, discharge rate from storage, and the availability of different options.
8. Currently, hydrogen is commonly stored in compressed or liquid forms.
9. The majority (85%) is produced on-site, with a small amount (15%) being transported.
10. Hydrogen usage can be categorized into short-term (point of export) and long-term (addressing seasonal changes).
11. Storage options include geological storage for large-scale and long-term needs and tanks for small-scale and short-term applications.
12. The conclusion of the report emphasizes the assessment of costs related to various methods of hydrogen production and storage, taking into consideration their maturity levels. Top of Form
13. Top of Form
14. Top of Form
15. In light of the intrinsic safety of the storage systems, the concluding statement emphasizes that, in the event of a ballistic penetration or explosion, storing hydrogen under pressure does not provide more serious safety risks than liquid fuel.

#### **REFERENCES**

1. D.S. Tarnay Hydrogen production at hydro-power plants Int J Hydrogen Energy(1985)

2. S.E. Hosseini et al. Hydrogen production from renewable and sustainable energy resources: promising green energy carrier for clean development *Renew Sustain Energy Rev* (2016)
3. D. Iribarren et al. Environmental and exergetic evaluation of hydrogen production via lignocellulosic biomass gasification *J Clean Prod* (2014).
4. F. Yilmaz et al. Thermodynamic performance assessment of ocean thermal energy conversion based hydrogen production and liquefaction process *Int J Hydrogen Energy* (2018)
5. S. Seyam et al. Analysis of a clean hydrogen liquefaction plant integrated with a geothermal system *J Clean Prod* (2020)
6. I.A. Hassan et al. Hydrogen storage technologies for stationary and mobile applications: review, analysis and perspectives *Renew Sustain Energy Rev* (2021)
7. R.R. Ratnakar et al. Hydrogen supply chain and challenges in large-scale LH<sub>2</sub> storage and transportation *Int J Hydrogen Energy* (2021)
8. S. Dutta A review on production, storage of hydrogen and its utilization as an energy resource *J Ind Eng Chem* (2014)
9. M. Fischer Utilization of solar and nuclear energy for hydrogen production *Nucl Eng Des* (1987)
10. M. Aziz et al. Hydrogen production from biomasses and wastes: a technological review *Int J Hydrogen Energy* (2021)
11. M. Rezaei et al. Wind energy utilization for hydrogen production in an underdeveloped country: an economic investigation *Renew Energy* (2020)
12. B. Widera Renewable hydrogen implementations for combined energy storage, transportation and stationary applications *Therm Sci Eng Prog* (2020).
13. J. Kurtz et al. Review of transportation hydrogen infrastructure performance and reliability *Int J Hydrogen Energy* (2019).
14. B.L. Salvi et al. Sustainable development of road transportation sector using hydrogen energy system *Renew Sustain Energy Rev* (2015).
15. A.E. Farrell et al. A strategy for introducing hydrogen into transportation *Energy Pol* (2003).
16. J. Gimbut et al. Recent trends in hydrogen production and utilization *Int J Hydrogen Energy* (2021).
17. K. Jangam et al. Perspectives on reactive separation and removal of hydrogen sulfide *Chem Eng Sci* (2021).
18. M. Al-Zareer et al. Analysis and assessment of a hydrogen production plant consisting of coal gasification, thermochemical water decomposition and hydrogen compression systems *Energy Convers Manag* (2018).